

## SECTION 8-JOINERY

खण्ड 8- बढईगिरी

## PER SQUARE METRE

- 08136 All as per Item No 08135 above but 12mm thick both side printed solid PVC plastic ply sheet and 5mm thick printed heat moulded 'C channel→
- 08137 All as per Item No 08135 above but 12mm thick both side prelam PVC plastic ply sheet and 5mm thick prelam heat moulded 'C channel

| S & F   | Fixing only |
|---------|-------------|
| Rs.     | Rs.         |
| 1367.00 | 42.00       |
| 1474.00 | 42.00       |

## SOLID PVC FRAME

## RUNNING METRE

- 08138 Solid PVC frame (Single Rebated) of size 60mm x 30mm made out of solid PVC foam with homogenous fine cellular structure having smooth outer integral skin with suitable metal stiffner and fixed with 100 x 8 sheet metal CSK screws complete all as specified and as shown on drawing (Note :- Door frame shall be water proof, termite proof, elegant and should have excellent screws holding strength to fix hinges and hold doors properly for a long life) →

| S & F  |
|--------|
| Rs.    |
| 529.90 |

## SQUARE METRE

- 08139 Factory made solid PVC profiled panel door shutter 28mm thick with integral skin as frame & 3mm thick high pressure compact laminate on both side of approved colour as infill, with 'C type GI or 40 x 20 x19 of MS pipe as stiffner & supplying & fixing in frame at site as per specifications & drawing. →

| S & F   |
|---------|
| Rs.     |
| 2055.70 |

- 08140 Supply and fix 30mm thick single piece, coloured ABC (ACRYLONITRILE BRUTADINE STYRENE) coated, PUF filled door shutters with PUF (Poly Urethane

## SECTION 8-JOINERY

खण्ड 8- बढईगिरी

## SQUARE METRE

Foam) insulation of minimum density 40 Kg/Cum filled in between two ABS sheets of thickness 1.2mm (min), border covered with insitu pasted ABS strips of width equal to thickness of door shutters, 1.2mm thickness, reinforced with two number 10mm CTD bars, pre-embedded with wooden blocks of suitable sizes for receiving hinges, tower / sliding bolts, towel rails, handles etc, with/without embossed pattern. →

- 08141 Supply and fix 30mm thick single piece, coloured ABC (ACRYLONITRILE BRUTADINE STYRENE) coated, PUF filled door shutters with PUF (Poly Urethane Foam) insulation of minimum density 40 Kg/Cum filled in between two ABS sheets of thickness 1.2mm (min), border covered with insitu pasted ABS strips of width equal to thickness of door shutters, 1.2mm thickness, reinforced with two number 10mm CTD bars, pre-embedded with wooden blocks of suitable sizes for receiving hinges, tower / sliding bolts, towel rails, handles etc, with/without embossed pattern. →

| S & F   |
|---------|
| Rs.     |
| 1811.80 |
| 1817.80 |